

# NB800 UMTS

## Wall-Mounted Industrial Router with UMTS and Ethernet



**The NB800 enables robust Internet connection for vending machines or ticketing. Its modular design supports a wide range of protocols addressing the fast developing Internet of Things (IoT).**

The industrial grade router provides key technologies to access any kind of applications in the Internet, but also Intranet sites and remote stations which can be connected via its powerful VPN protocol suite including OpenVPN and IPsec.

The integrated modem supports UMTS networks and ensures WWAN connectivity. Ethernet and USB open further possibilities to integrate sensors and actuators easily into the network. A hardware shield concept brings additional flexibility to turn the NB800 into an application specific tailored device (OEM) or to follow the technology changes. By now, shields with dual CAN or digital I/Os and serial interfaces are available.

The durable aluminum housing suitable for wall-mounting in combination with the supported temperature range -40 °C to 70 °C stands for its robustness. NB800 resists mechanical and thermal stress.

The router software is based on well proven components including an embedded Linux operating system and a wide range of communication and routing protocols as VLAN, Mobile IP, OSPF, BGP and RSTP. It's possible to run customer applications in a LXC Container. An SDK gives programmers a great tool to implementing all kind of applications with simple scripts. Data preprocessing can be done directly on the router, thus saving an additional IPC. Other features include a smart Link Manager for optimized cellular connections, Quality of Service (QoS) for an efficient data exchange, E-Mail and SMS for alarming and notifications, a web server and RADIUS authentication.

### Applications

- Industrial IoT
- Smart Home
- ATM, POS
- CCTV
- Digital signage
- Electronic payment
- Condition monitoring

### Key Features

- UMTS/GSM
- Ethernet
- Expandability by shields
- NetModule Router Software
- SDK Scripting & LXC
- Small form factor
- Fanless

### Performance

- 600 MHz CPU
- 100 Mbps routing performance

### Sprzedaż i dystrybucja

**KARCZ Polska  
ul. Wilczak 16A  
61-626 Poznań**

**tel.: 602362236, 61 8273090**

**[www.karcz.eu](http://www.karcz.eu)**

## Specifications

Mobile / Cellular	<p>1 Multimode UMTS and GSM module            3G - UMTS/HSPA: B8(900MHz), B1(2100 MHz)            2G - GSM/GPRS/EDGE: B5(850 MHz), B8(900 MHz), B3(1800 MHz), B2(1900 MHz)            Data rate: max. 21.6 Mbps downlink / 5.76 Mbps uplink (HSPA+)            1 SMA antenna connector            1 Micro SIM (3FF) ETSI TS 102 221 V9.0.0, Mini-UICC</p>
Ethernet	1 Ethernet port, 10/100 Mbps, auto MDIX - Connector type: RJ45
USB	USB 2.0 Host Port, USB A connector type
Shields (Optional)	<p>COM/IO shield:            Protocols: RS-232 (RXD, TXD) or RS-485 (D+, D-) configurable            Bit Rates: up to 1Mbps; RS-485 bus termination: 120R (configurable)            1 DI: level 0 (0-3VDC), level 1 (9-36VDC), isolation: 1500VAC            1 DO: 0-36VDC/1A; isolation: 1500VAC            -- or --            2xCAN shield:            Bit rates: up to 1Mbps; bus termination: 120Ohms (configurable)            --            Extension connector: 6 pin terminal block, 3.5 mm pitch</p>
Storage	4GB internal
Power	<p>Nominal Input Voltages: 12VDC (+/-20%), 24VDC (+/-20%)            Average power consumption: 5W            Connector type: 2 pin terminal block, 3.5 mm pitch</p>
Environment	<p>Operational temperature: -40 °C to +70 °C; Storage temperature: -40 °C to +85°C            Ingress Protection Rating: IP40</p>
MTBF	>440.000h depending on model
Dimensions, weight	Width 85/111mm x height 32mm x depth 110mm, ca. 250g
Compliance	<p>CE according to 2014/53/EU (RED), 2011/65/EU (RoHS), 2012/19/EU (WEEE), 1907/2006/EC (REACH)            FCC according to 47 CFR, Part 15B</p>
Standards	<p>EN 62368-1, EN 62311, EN 55024, EN 55032, EN 61000-6-2, EN 61000-6-3, EN 301 489-1, EN 301 489-7, EN 301 489-17, EN 301 489-24, EN 300 328, EN 301 511, EN 301 893, EN 301 908-1, EN 301 908-2, EN 301 908-13</p>
Order numbers NB800-USu	(contact sales for more models, options or project specific adaptations) UMTS/GSM Router + USB

**KARCZ Polska, ul. Wilczak 16A, 61-626 Poznań, tel: 61 827 3090, 602 362236**

### NetModule AG

Meriedweg 11  
3172 Niederwangen

T +41 31 985 25 10  
F +41 31 985 25 11

Switzerland

### NetModule GmbH

Frankfurter Strasse 92  
65760 Eschborn

T +49 6196 77 99 79 0  
F +49 6196 77 99 79 9

Germany